

04/01/2010 03:33 PM

```
> Regarding how we would use the EFDC model and why:
```

>
>
> As part of the remedial design for the areas of potential concern
> (AOPCs), it is necessary to analyze the effects that proposed changes in
> bathymetry have on river stage height. This analysis is typically
> conducted using a one-dimensional hydrodynamic model that predicts stage
> height changes caused by changes in the cross-sectional area of the
> river. For the Lower Willamette River (LWR), a two-dimensional
> hydrodynamic model already exists and it is based on the Environmental
> Fluid Dynamics Code (EFDC) framework (Hamrick 1992). This model has
> been calibrated and validated for the LWR and deemed reliable for
> evaluating its hydrodynamic behavior. Therefore, we propose to use this
> model to analyze the potential effects of proposed remedial alternatives
> on stage height during flood events.
>

>
> EFDC is a modeling framework capable of performing two- or
> three-dimensional hydrodynamic simulations and it has been approved by
> the U.S. Environmental Protection Agency (EPA). This model has been
> successfully applied in numerous hydrodynamic, sediment transport, and
> chemical fate studies. Using this framework, a two-dimensional,
> vertically-averaged model of the LWR has been developed by the Lower
> Willamette Group (LWG). The model domain extends from Willamette Falls
> to the confluence with the Columbia River. This model has been
> calibrated to measured water stage heights and current velocities
> collected at several locations. The model is currently being used for
> the RI/FS study of the LWR, with the hydrodynamic results being used to
> drive sediment transport and chemical fate models.
>

>
> This hydrodynamic model is sufficiently reliable for analyzing the
> effects of bathymetry changes on river stage height. Thus, development,
> calibration and application of a one-dimensional hydrodynamic model are
> not necessary. Most importantly, the predictions of the two-dimensional
> model will be at least as accurate, and probably more accurate, than a
> one-dimensional model, mainly because the two-dimensional model provides
> a more realistic representation of the geometry and bathymetry of the
> LWR. This characteristic of the two-dimensional model makes it possible
> to simulate recirculation patterns and backwater effects that locally
> modify river stage height, which are small spatial scale features that
> are not captured by a one-dimensional model. Therefore, there is no
> need to develop a new one-dimensional model of the LWR that will, at
> best, provide the same results as the existing two-dimensional model.
>

> Reference

>
> Hamrick, J.M. 1992. A Three-Dimensional Environmental Fluid Dynamics
> Computer Code: Theoretical and Computational Aspects. College of
> William and Mary, Virginia Institute of Marine Sciences. Special Report
> 317. 63 pp.
>

> Regarding Reasons Why We Want to Use EFDC:

>
> Per the above EFDC will be more accurate and capture smaller scale
> features than developing a new 1-D HEC-RAS model. Also, given that the
> EFDC model is all set up and calibrated, there will be very little
> additional time to run the flooding simulations. In contrast, if we use
> HEC-RAS we will have to parameterize, troubleshoot, and calibrate an
> entirely new model for the river. We are completely familiar with
> HEC-RAS and its various uses, but even so, it will take significant
> additional time (and cost) to develop and calibrate an entirely new
> model. We do not need to purchase the model software (we already have
> it). None the less, the labor effort associated with developing and
> calibrating an entirely new model for the site are significant and we
> estimate in the range of \$40 to \$50K in labor costs. Given that EFDC
> will be both more accurate and cost less to use, the LWG prefers the use
> of EFDC for this purpose.
>

> Thanks.
>

> Carl
>

> Carl Stivers
>

> ANCHOR QEA, LLC
>

> cstivers@anchorqea.com
>

> 23 S. Wenatchee Ave, Suite 120
>

> Wenatchee, WA 98801
>

> Phone: 509.888.2070

>
>
> Fax: 509.888.2211
>
>
>
>
>
> ANCHOR QEA, LLC
>
> www.anchorqea.com
>
>
> Please consider the environment before printing this email.
>
>
> This electronic message transmission contains information that may be
> confidential and/or privileged work product prepared in anticipation of
> litigation. The information is intended for the use of the individual
> or entity named above. If you are not the intended recipient, please be
> aware that any disclosure, copying distribution or use of the contents
> of this information is prohibited. If you have received this electronic
> transmission in error, please notify us by telephone at (206) 287-9130.
>
>
> -----Original Message-----
> From: Humphrey.Chip@epamail.epa.gov [
> mailto:Humphrey.Chip@epamail.epa.gov]
> Sent: Thursday, April 01, 2010 3:03 PM
> To: Carl Stivers
> Subject: RE: Flood analysis
>
>
> Carl
>
>
> Can you send me a short description of how you would intend to use the
>
> ERDC model in lieu of the HEC RAS model for predicting flood rise as
>
> part of the FS & reasons why (including the cost savings of not having
>
> to purchase the software) you want us to consider this? I need to send
>
> it around and want to make sure I capture your perspective correctly.
>
> If you've already provided something just point me to it.
>
>
> thanks
>
> Chip
>